

## JACK 6 ZOOM

Adjustable downlights

design Lapo Grassellini



An orientable recessed dark light with an adjustable light beam from 10° to 55°, in order to adapt to the project needs.

Incasso orientabile ad ottica arretrata darklight con fascio luminoso regolabile da 10° a 55°, per adattarsi alle necessità progettuali.

Appareil encastrable orientable à optique en retrait darklight à faisceau lumineux réglable de 10° à 55°, pour s'adapter aux nécessités conceptuelles.

Einstellbares Einbau-Dunkel-Licht mit einstellbarem Lichtstrahl von 10° bis 55°, damit er sich den gestalterischen Anforderungen anpasst.

Luminaria empotrable orientable óptica hacia atrás darklight con haz luminoso regulable de 10° a 55°, para adaptarse a las necesidades de diseño.




IP20 made in Italy

**Supply current**  
500mA (V, 9V)

**Power**  
6W

**Dimensions**



**Adjustable optics**  
10°-55°

**CCT/CRI/Flux**

| CCT   | CRI | Flux (lm) |
|-------|-----|-----------|
| 2700K | 98  | 540       |
| 3000K | 98  | 600       |
| 4000K | 98  | 620       |

**Code construction**

| JKZ   | X     | X     |
|-------|-------|-------|
| 2     | 3     | 4     |
| 2700K | 3000K | 4000K |
| 1     | 2     | 5     |
| White | Grey  | Black |

**Optionals**

**AL7022**  
24VDC/500mA constant current converter

**Drivers**

| on/off                          | dimmable                              |
|---------------------------------|---------------------------------------|
| 500 mA                          |                                       |
| AL1074 (1.2)<br>30mm IP20       | AL4010 (1.4)<br>72mm IP20 PUSH 1..10V |
| AL1077 (1.2)<br>40mm IP20       | AL4151 (1.4)<br>72mm IP20 DALI        |
| AL1084 (1..3)<br>55mm IP20 S.P. | AL4153 (1.4)<br>60mm IP20 IGBT-TRIAC  |
| AL9051 (1..3)<br>60mm IP67      |                                       |