



SRD11-09

SmartLight™

Design. Engineering. Quality. Service.



Power

9 W

Light Source

EPISTAR

CCT

Y | W | C

Luminous  
flux

675 lm

L/B x H  
(mm)

110 x 37

Beam Angle

80°

Ø (mm)

84

IP Rating

IP 44





## SRD11-12

**SmartLight™**

Design. Engineering. Quality. Service.



Power

12 W

Light Source

EPISTAR

CCT

Y | W | C

Luminous  
flux

900 lm

L/B x H  
(mm)

140 x 45

Beam Angle

80°

Ø (mm)

125

IP Rating

IP 44







## SRD11-16

**SmartLight™**

Design. Engineering. Quality. Service.



Power

16 W

Light Source

EPISTAR

CCT

Y | W | C

Luminous  
flux

1200 lm

L/B x H  
(mm)

190 x 58

Beam Angle

80°

Ø (mm)

150

IP Rating

IP 44





## SRD11-25

**SmartLight™**

Design. Engineering. Quality. Service.



Power

25 W

Light Source

EPISTAR

CCT

Y | W | C

Luminous  
flux

1875 lm

L/B x H  
(mm)

225 x 62

Beam Angle

80°

Ø (mm)

200

IP Rating

IP 44

